

WSC 255-KE (110 V)



Technical Data

Weight	4.3 kg
Maximum Blade Diameter	160 mm
Minimum Blade Diameter	144 mm
Inside Diameter of Extraction Connector	35 mm
Cutting Depth at 45 Degrees	0 - 43 mm
No Load Cutting Speed	36 m/s
Under Load Cutting Speed	36 m/s
Input power	1400 W
No Load Speed	4300 rpm
Output Power	790 W
Rated voltage	110 V
Bore Size	20 mm
Impact and Vibration	< 2.6 m/s ²
Noise Power Level	< 102 dB (A)
Noise Pressure Level	< 89 dB (A)
Protection Class	II / double-insulated as per EN 50 144
Riving Knife Thickness	1.3 mm
Supply Cord Length	5 m
Sustained Sound Pressure Level	89 dB
Base materials	Chipboard, Solid wood, Laminate-faced plastic particle board, Construction timber
Radio and TV Interference Suppression	As per EN 50 014
Package content	Comprising: Hex, socket wrench, shifting riving knife, rotatable carbide-tipped "multiCut" saw blade (160 mm dia. positive altern operating instructions and safety precautions. Packed in an impact toolbox
Trades	Joiners, Shopfitting, Kitchen installers, Interior finishing, General Carpenters, Roof
Cutting Depth at 0 Degrees	0 - 55 mm
Approvals	CE