



BOM			
Item	Description	Quantity	
1	Dual Locking Castors	4	
2	500mm Adjustable Leg	4	
3	2 Rung 1m Ladder Frame	0	
4	2 Rung 1m Span Frame	0	
5	3 Rung 1.5m Ladder Frame	0	
6	3 Rung 1.5m Span Frame	0	
7	4 Rung 2m Ladder Frame	1	
8	4 Rung 2m Span Frame	1	
9	Trap Door Platform	1	
10	Standard Platform	0	
11	Horizontal Brace (red trigger)	6	
12	Diagonal Brace (blue trigger)	2	
13	(New style) Complete Toe-board Se	et 1	
14	Standard Stabiliser	0	
15	Jumbo Stabiliser	0	
16	Instruction Manual & BSEN1004 certificate of conformity	1	

Technical Information

W

ph

L

Base Dimensions:	<i>(L)</i> 2.5m X <i>(W)</i> 0.85m
Maximum Platform Height (ph): 1.2m
Maximum Working Height (wh	<i>ı)</i> : 3.2m
Maximum Working Load Per F	Platform: 275kg
Maximum Working Load Per T (including tower weight)	Fower: 950kg
Weight:	83kg





At Towers and Sanders we pride ourselves on building our products in the UK giving you the best quality and service. All our scaffold towers are certified to BS EN1004